



NOTES:

MATERIALS

- HOUSING:
HI-TEMP.PLASTIC UL 94V-0 BLACK
- CONTACT
COPPER ALLOY,T=0.15mm
GOLD PLATED ON CONTACT AREA
GOLD FLASH PLATED ON SOLDER TAILS UNDER NICKEL PLATED
- SHELL:
STAINLESS STEEL OR COPPER ALLOY T=0.25mm
MATTE TIN PLATING OVERALL UNDER NICKEL PLATED

SPECIFICATIONS

- VOLTAGE RATING:30V AC
- CURRENT RATING:WHEN APPLYING CURRENT ONLY TO SIGNAL TERMINALS:
1.0A(FOR TERMINAL NO.2,3 AND 4)
WHEN APPLYING CURRENT ONLY TO POWER TERMINALS:
1.8A(FOR TERMINAL NO.1 AND 5)
0.5A(FOR TERMINAL NO.2,3 AND 4)
- INSULATION RESISTANCE:100M MIN/AT 100V DC
- DIELECTRIC WITHSTANDING VOLTAGE:100V(r.m.s)AC FOR 1 MINUTE
- CONTACT RESISTANCE:30m MAX.
- OPERATING TEMPERATURE:-30 TO +80?

GENERAL TOLERANCE		DWG NO.	JYSA0620-001	APPD:	WMD	Scale	1:1
X.±0.45	x.±5'	Title	MICRO USB 5PIN	CHKD:		UNIT	mm
X±0.35	x.±2'		拆板1.0 DIP9.45 无翻边	DR:			
.XX±0.25	.xx.±1'	Part NO.	JYS-USB945-017	Date	2013/02/29		
.XXX±0.15	.xxx.±0.5'						
SHEET	1/1	杰宇森 电子有限公司 JIE YU SEN ELECTRONIC CO., LTD.					

REV.	EGN.NO.	MODIFY CONTENT	DATE
A		NEW	2011/10/31