



RECOMMENDED PCB LAYOUT  
TOP VIEW (.XX±0.05)

性能：  
 额定电流：2.0A  
 额定电压：12V  
 耐电压：500V  
 接触电阻：30mΩ  
 绝缘电阻：500MΩ  
 工作温度：-40℃~+85℃  
 塑件（材质）：LCP  
 接触点（材质）：磷铜，镀金

PART NO.	H=?	DIM A	DIM B
JYS-BY240-143	2.4	2.4	4.2
JYS-BY300-144	3.0	3.0	4.8
JYS-BY350-145	3.5	3.5	5.3

GENERAL TOLERANCE		DWG NO.	JYSA1014-03	APPD:	WIND	Scale	1:1
X±0.45	x:±5°	Title	BATTERY SPIN 2.50PITCH	CHKD:		UNIT	mm
X±0.35	x:±2°	Part NO.	2.4H-3.5H 有柱	DR:			
.XX±0.25	.xx'±1'		SEE TABLE	Date	2011/10/31		
.XXX±0.15	.xxx'±0.5'						

JYS 杰宇森电子有限公司  
 JIE YU SEN ELECTRONIC CO., LTD.

REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2011/10/31